ECO-irrigation



Netafim has developed the "Eco-irrigation" specially for outdoor irrigation. This is a black HDPE pipe with grey stripe. Eco-irrigation is tested according to the applicable standards for PE80 pipe.

APPLICATION

Eco-irrigation is outstandingly suitable for outdoor irrigation for outdoor crops

CHARACTERISTICS

- Durable production pipe
- Made from selected reclaim grades
- Special recipe for optimum characteristics and long service life
- Lightweight line, ideal for export

TECHNICAL DATA

PE grade : HDPE
Diameter : 32 - 250 mm
Max. working pressure : 6.3 bar

Appearance : black

: black pipe with grey strip and imprint "Eco-Irrigation", diame-

ter and pressure class

Standards : PE80 standard (according to

NEN-EN 13244-2 and NEN-EN

12201-2),

not suitable for drinking water

applications

INSTALLATION & MAINTENANCE

Note: Never use detergents during assembly and use with PE material.

- Eco-irrigation is not suitable for punching.
- Standard PE couplings must be used with this pipe.
- Eco-irrigation is intended for outdoor irrigation.

Coil and pipe lengths for ECO-irrigation

	HDPE 6,3 bar SDR21			
diameter (mm)	L=10m	R=50m	R=100m	
32		Χ	Х	
40		Χ	Х	
50		Χ	Х	
63	Х	Χ	Х	
75	Х	Χ	Х	
90	Х	Χ	Х	
110	Х			
125	Х			
160	Х			
200	Х			
250	Х			
250	Х			

L = Supplied in straight lengths

Consult portfolio overview for availability



R = Supplied in coil

x = Producible - other sizes on request