DAN deflectors



DAN deflectors

Eight available deflectors which determine the spray pattern. Suitable for modular DAN sprinklers with

Red (180°) narrow

- Single-sided, smooth, small deflector, is used as a edge sprinkler for irrigation with DAN-8991 / **DAN Bridgeless**
- ✓ Up to 45 I/h sprinklers
- Range sufficient for sprinklers up to 1.5 meters, as well as sprinklers up to 2 meters

Red (180°) standard

- Single-sided, ribbed, large deflector, is used as an edge sprinkler for irrigation with DAN-8991 / **DAN Bridgeless**
- ✓ From 70 l/h sprinklers
- Range sufficient for sprinklers up to 1.5 meters, as well as sprinklers up to 2 meters

Black (90°)

- Angled deflector for small surfaces and in garden irrigation
- ✓ Can be installed upright (for garden) irrigation)

- Orange (360°) OProvides a narrow conical spray pat-
 - ✓ Very small range up to approx. 1.0
 - Installed upright, can be used between (cherry) trees to irrigate the soil while keeping the tree trunk dry

- Yellow (360°) ✓ Round deflector with small range (up to 3 meters diameter)
 - Is used in greenhouses above panels, with and without anti-mist element
 - Can be installed upright (for garden irrigation)

Violet (mist)

- Mist deflector for fine sprays
- In combination with violet and brown nozzle
- Range up to 1.8 meters, 360°

Blue (strip)

- Gives an elongated spray pattern
- Is used for under-tree irrigation
- Range from 3.2 to 9 meters, depending on flow rate

- pattern
 - Range from 2.5 to 6 meters, depending on flow rate

