

# PVC glue & Tangit cleaner

Henkel



Tangit glues from Henkel are suitable for gluing PVC in industry, horticulture and plumbing applications. The range comprises Tangit All Pressure and Tangit Cleaner.

## CHARACTERISTICS

### Tangit All Pressure:

- ✓ Available in packages of 250, 500, 1000 and 4500 grams
- ✓ Gap-filling glue (up to 0.8 mm) for PVC-U
- ✓ For applications up to 16 bar
- ✓ Special brush for quick glue application
- ✓ Standard installations
- ✓ Suitable for gluing fertiliser units and systems
- ✓ KIWA-certified up to 90 mm and KOMO-certified from 40 to 160 mm

### Tangit Cleaner:

- ✓ Universally applicable for rigid PVC, PVC-C and ABS
- ✓ Free from toluene and methylene chloride
- ✓ Less formation of condensation and ice after use

## INSTALLATION & MAINTENANCE

### General

- ✓ Follow the manufacturer's instructions.
- ✓ Product data sheets and safety data sheets are available on request.
- ✓ The special Dytex glue is available for highly concentrated acids.



## TECHNICAL DATA

		Tangit All Pressure	Tangit Cleaner
Certification		KIWA and KOMO	-
Viscosity at 23 °C	mPa.s	1800 - 3500	-
Density	g/ml	0,960	0,820
Open time		max. 4 min.	n/a
Consumption per 100 joints	kg	1,1 (32-40 mm)	0,7 (32-40 mm)
Cleaning agents		Tangit Cleaner	-
Processing temperature	°C	min. 5	min. 5
Storage temperature	°C	cool and dry (min. 5)	cool and dry (min. 5)
Heat resistance	°C	60	-
Shelf life	months	24	12
Maximal final strength	hours	> 24	-